Automation for a Changing World

Delta Human Machine Interface
DOP-100 Series

www.deltaww.com

DELTA

Smarter. Greener. Together.

Advanced Human Machine Interface for

The DOP-100 Series Human Machine Interfaces include a Basic HMI, Standard HMI and Advanced HMI for different applications. The HMIs adopt the latest Cortex-A8 / Dual Core high-speed processor and 65,536 color LCD screen with high brightness and contrast. In addition, they are equipped with the HMI programming software DOPSoft 4.0 and built-in Lua editor for easy programming as well as alarm / history log / user authority functions for highly efficient management.

With advanced communication capabilities and enhanced functions, the DOP-100 Series elevates machine efficiency to bring more value to our customers, and to achieve "Automation for a Changing World"!

Advanced Display

Standard HMI

Features General and Ethernet Types for various applications

Advanced HMI

Features narrow frame design, supports various network communications, multilingual input and multimedia functions

Future Industry

Basic HMI

Simple operating structure for harsh environments

Handheld HMI

Customized for the teaching needs of various motion platforms such as robotic arms

Table of Contents

Introduction 2

Model Selection
Advanced HMI
Standard HMI
Basic HMI

Robust Hardware 16

Power Isolation
Fully Isolated Communication Interface
PCB Coating

Programming Software – DOPSoft 4.0 17

Abundant Elements
Smooth Animation
User-Friendly Programming Interface
Editing Windows

Advanced Alarm 22

Alarm Functions

Data Management 24

Historical Data
Historical Data Review
Zoom In / Out Display
Recipes
PDF for Data Review

User Authority Management 26

Account and Authorization Management
Operation Log

Cloud Integration 27

FTP Server
VNC Server
Web Monitoring

Product Information 28

Hardware Specifications
Model Description
Dimensions

Easy Model Selection

The DOP-100 Series offers complete models for different applications. Users can easily select a suitable HMI based on size or function easily

B Type	1 COM port
D Type	1 COM port + 1 Ethernet port
C Type	2 COM ports
E Type	2 COM ports + 1 Ethernet port
I Type	3 COM ports + 1 Ethernet port
H Type	Handheld HMI + 1 Ethernet port or 422/485 COM ports
W Type	More than 1 COM port + 1 Ethernet port + Narrow frame design + Multi-language
M Type	2 COM ports + 2 Ethernet ports + Narrow frame design + Multi-language + Multi-media

Type Definition

DOP-107 W V


Advanced HMI
At least 1 COM Ports &
1 Ethernet prot included
W Type
Advanced Narrow Frame
M Type
Advanced Multimedia
Handheld HMI
1 Ethernet port or 422/485
COM ports
H Type
Handheld
Standard HMI
At least 2 COM Ports
included
C Type
Standard General
E Type
Standard Ethernet
(2COM)
I Type
Standard Ethernet
(3COM)
Basic HMI
1 COM Ports included
B Type
Basic
D Type
Basic Ethernet

Advanced HMI

The Advanced HMI adopts a wide screen and narrow frame design. It supports Ethernet communication & multilingual inputs. The Multimedia Type DOP-112 / 115 offers multimedia functions to meet different applications.

M Type W Type

Features

Narrow Frame
Enlarged visual display for better user experience

LUA Language
Simple and easy structural programming language to meet various demands

Pressing times >10,000,000
Effective pressing times increased through strict endurance tests

IP65 Rating
The front case protects the HMI from, rain, and dust

Multilingual Input
16 different languages input for easy operation

Diagnostics Function
Collects and solves issues remotely

Power Isolation
Protects the HMI from accidental surge interference

VNC Remote Monitoring
Remote control with mobile devices

QRcode Scanning
Generates QRcodes with self-defined content for mobile device identification

Supports GIF Graphic Elements
Easy setting to play vivid GIF elements

Embedded Linux System
Open system for flexible and stable program development

DOPSoft 4.0
New software DOPSoft 4.0 offers more complete functions and a better interface

Operating Temperature 0ºC ~ 50ºC
Compliant with industrial operating environments

CE / UL Certified
Compliant with CE and UL standards

Multimedia Functions
Captures image with an external camera or replays important recordings

M Type Only

Ethernet Communication
Connects to a master device or PLC with high-speed Ethernet communication

Communication Isolation
COM and Ethernet ports with built-in isolation circuits enhance communication stability

OPC UA
Supports M2M communication and data transmission among machines from various manufacturers for diverse industries

FTP/eMail Supported
Simple data transmission and real-time status report

Supports PDF and TXT Reader
PDF and TXT files supported

Camera & Video Play
Multi-Media Functions

Analog Camera

Supports external camera via analog, suitable for capturing fast and short-distanced images

Applications: Textiles | Pharmaceutical | Rubber & Plastics

IP Camera

Supports IP Camera via Ethernet, suitable for capturing remote and wide-range images

Applications: Packaging | Logistics | Mining | Power Generation | Oil & Gas

VGA Input

Displays images from external devices such as machine vision systems, PCs or notebooks

Video Play

Views mpeg4 files captured by analog or IP camera from internal storage or USB disk / SD card

Event Trigger

HMI performs specific actions when an event condition occurs
Sets up event trigger conditions to capture images and archive as mpeg4 files

Multi-Language Input for Localization

- The Advanced HMI supports multilingual inputs for:
  - Recipe Name (ENRCPG)
  - Recipe Group Name (ENRCPNO)
  - Recipe Content (Char)
  - User Name



- Supports 16 languages: English, Traditional Chinese, Simplified Chinese, French, German, Russian, Japanese, Korean, Spanish, Portuguese, Hindi, Turkish, Arabic, Persian, Italian and Polish

OPC UA

Delta' HMI can implement M2M communication and data transmission for diverse industries by means of OPC UA. Communication among different manufacturers' machines is enabled through information modeling.

Standard HMI

The Standard HMI is equipped with 2 COM ports to meet most applications. It also offers Ethernet Types for fast and easy connection with other equipment.

C Type E Type I Type

Features

Embedded Linux System
Open system for flexible and stable program development

LUA Language
Simple and easy structural programming language to meet various demands

DOPSoft 4.0
New software DOPSoft 4.0 offers more complete functions and a better interface

Pressing times >10,000,000
Effective pressing times increased through strict endurance tests

Operating Temperature 0ºC ~ 50ºC
Compliant with industrial operation environments

IP65 Rating
The front case protects the HMI from rain, and dust

CE / UL Certified
Compliant with CE and UL standards

Diagnostics Function
Collects and solves issues remotely

Ethernet Communication
Connects to master device or PLC with high-speed Ethernet communication

E Type I Type

Power Isolation
Protects the HMI from accidental surge interference

Communication Isolation
COM and Ethernet ports with built-in isolation circuits enhance communication stability

E Type I Type

VNC Remote Monitoring
Remote control with mobile devices

E Type I Type

FTP/eMail Supported
Simple data transmission and real-time status report

E Type I Type

Supports PDF and TXT Reader
PDF and TXT files supported

Supports GIF Graphic Elements
Easy setting to play vivid GIF elements

User-Friendly
Intuitive operation interfaces for users

Basic HMI

The Basic HMI features basic functions and easy installation for industrial applications. With an IP65 water-proof rating, it is suitable for harsh environments.

B Type D Type

Features

Embedded Linux System
Open system for flexible and stable program development

LUA Language
Simple and easy structural programming language to meet various demands

DOPSoft 4.0
New software DOPSoft 4.0 offers more complete functions and a better interface

Pressing times >1,000,000
Effective pressing times increased through strict endurance tests

Operating Temperature 0ºC ~ 50ºC
Compliant with industrial operating environments

IP65 Rating
The front case protects the HMI from rain, and dust

CE / UL Certified
Compliant with CE and UL standards

Diagnostics Function
Collects and solves issues remotely

Ethernet Communication
Connects to master device or PLC with high-speed Ethernet communication
D Type Only

FTP/eMail Supported
Simple data transmission and real-time status report
D Type Only

Communication Isolation
COM and Ethernet ports with built-in isolation circuits enhance communication stability
D Type Only

VNC Remote Monitoring
Remote control with mobile devices
D Type Only

Supports PDF and TXT Reader
PDF and TXT files supported

Diagnostics Function
Collects and solves issues remotely

User-Friendly
Intuitive operation interfaces for users

Handheld HMI

The handheld human-machine interface adopts a lightweight handheld design and can choose to support Com communication (422/485) or Ethernet communication. Meet the teaching needs of various motion platforms such as robotic arms.

H Type

Features

Embedded Linux System
Open system for flexible and stable program development

LUA Language
Simple and easy structural programming language to meet various demands

DOPSoft 4.0
New software DOPSoft 4.0 offers more complete functions and a better interface

Pressing times >10,000,000
Effective pressing times increased through strict endurance tests

Operating Temperature 0ºC ~ 50ºC
Compliant with industrial operating environments

IP54 Rating
The front case protects the HMI from rain, and dust

CE Certified
Compliant with CE standards

Diagnostics Function
Collects and solves issues remotely

Ethernet Communication
Connects to a master device or PLC with high-speed Ethernet communication

Power Isolation
Protects the HMI from accidental surge interference

Communication Isolation
COM and Ethernet ports with built-in isolation circuits enhance communication stability

FTP/eMail Supported
Simple data transmission and real-time status report

Supports PDF and TXT Reader
PDF and TXT files supported

QRcode Scanning
Generates QRcodes with self-defined content for mobile device identification

User-Friendly
Intuitive operation interfaces for users

Diagnostics Function
Collects and solves issues remotely

Robust Hardware

Power Isolation

- Complete series with built-in power isolation circuits provides the most complete protection against accidental external spikes



Fully Isolated Communication Interface

- Complete series has built-in COM and Ethernet isolation circuits to protect against noise that can occur from the grounding of various devices such as PLCs, servo drives, inverters and others

PCB Coating

- Complete series has PCB coating for enhanced durability and to protect against humidity and dust for applications in a range of environments



Model	Power Isolation	Communication Isolation
Advanced HMI (Multimedia Type)		
DOP-112/115 MX	Yes	Yes
Advanced HMI		
DOP-103WQ/107WV/110WS	Yes	Yes
DOP-112/115 WX	Yes	Yes
Handheld HMI		
DOP-107H	Yes	Yes
Standard HMI (Ethernet Type)		
DOP-107IV	Yes	Yes
DOP-108IG/110IG	Yes	Yes
DOP-110IS	Yes	Yes
DOP-107EV	Yes	Yes
DOP-107EG	Yes	Yes
Standard HMI		
DOP-105CQ	Yes	No
DOP-107CV	Yes	No
DOP-110CS	Yes	No
DOP-110CG	Yes	No
Standard HMI (General Type)		
DOP-107DV	No	No
Basic HMI		
DOP-103BQ	No	No
DOP-107BV	No	No

Programming Software – DOPSoft 4.0

Abundant Elements

- Abundant built-in element graphics for vivid interface display for a variety of industrial applications



Smooth Animation

- New smooth animation technology for realistic dashboard display



Programming Software - DOPSoft 4.0

User-friendly Programming Interface

Bookmark Management

Bookmark menu allows users to switch pages easily

Project Management Batch

Quickly switch items via the project branch feature

Editing Area

Provides real-time display of your edit

Output List

Automatically displays edit results of each screen. Users can review and resolve errors by clicking screens

Edit Preview

Quickly browses the overall project via edit preview





General Tool

Shortcut icons help enhance working efficiency

Property

Provides easier property setup via group lists

Property Quick Window

Standard accessory dialog box adopts built-in preview and quick-edit functions

Programming Software - DOPSoft 4.0

Editing Windows



Register View Window

The color blocks of red and white allow users to view the memory register status

Red blocks indicate the used registers

White blocks indicate empty registers

Macro Management Window

Users can view all types of macros in the project



Selected a macro via the list

Directly edit the macro after clicking



Lua Tool Bar

Program Debugging

Stops program debug

Program break point



Online Coding Tips

Lua editor displays tip windows of the codes when users move the mouse to selected codes

Parameter Monitoring Window

Allows users to monitor parameter variation during program development



Programming Assistance Window

Provides online assistance as follows:

- Lua code templates
- Program usage and properties
- Program samples

Advanced Alarm

Strengthened alarm functions allow users to easily manage machine operations and quickly eliminate problems

- Alarm messages contain current register data for issue analysis



Alarm Sorting

Alarm sorting via a "Sorting" function based on alarm attributes for quick information inquiries

Supports Compound Address Monitoring

Able to monitor Word and Bit documents at the same time



Versatile Alarm Triggering Conditions

Triggering conditions can be setup via a built-in function, no external editing programs required



Alarm Notification

Automatically sends out alarm notification emails to logged-in recipients when alarms occur and supports the Secure Sockets Layer (SSL) protocol to ensure safe data transmission

- Indicates the alarm trigger and recovery time, and provides alarm acknowledge time / date (Ack) to confirm and monitor troubleshooting progress

Message	Trigger	Ack	Recovery
Temp. too Low • PV is 12	15:07:12 02/03/2017		15:07:15 02/03/2017
Temp. too High • PV is 91	15:07:15 02/03/2017	15:07:56 02/03/2017	15:07:22 02/03/2017
Temp. too Low • PV is 15	15:07:22 02/03/2017		15:07:25 02/03/2017
Temp. too Low • PV is 23	15:07:28 02/03/2017	15:07:58 02/03/2017	15:07:34 02/03/2017

Alarm Filtering

Advanced address control filtering allows users to find specified alarm messages according to user needs

Action	
Address control filtering allows users to find specified alarms	
No.	Action
0	Preset state, shows all triggered alarms
1	Hide alarms with "Restore Time" and "Confirm Time"
2	Hide alarms with "Restore Time"
3	Hide alarms with "Restore Time" or "Confirm Time"
4	Hide alarms with "Confirm Time"

Alarm Ordering

Able to display alarms in the order of Trigger Time / Confirm Time / Restore Time



Data Management

Historical Data

- Able to generate historical reports with user-defined file names and timestamps through Bit Control





Historical Data Review

- Allows historical data review on backup in USB disk or SD cards

Zoom In / Out Display

- Zoom in / out function for convenient data viewing



Recipes

- Supports 2D and 3D recipe grouping, more flexible in building recipe database
- Various recipe formats, including text format (Unicode) which can also be used as formula notes

	D100	D101	D102	D103	D104	D105	D106
	D100	D101	D102	D103	D104	D105	D106
Cake Recipe 1	Strawberry	300	0	0	221.56	533.1	150.7
Cake Recipe 2	Chocolate	0	300	0	387.98	490.8	163.9
Cake Recipe 3	Vanilla	0	0	300	120.14	505.3	279.8
		Strawberry	Chocolate	Vanilla	Sugar	Flour	Milk
	Char	Unsigned DEC			Floating		

Recipe Group 2

Recipe Group 1

- Recipes can be saved in CSV files for convenient editing on PCs
- Allows recipe update or backup through USB disks, SD cards or FTP

PDF for Data Review

- Saves manuals or instruction PDF files in USB disks or SD cards for reference anytime

User Authority Management

Account and Authorization Management

- Supports 8 levels of authority and allows 8 accounts (account name/password) for each level
- Different function and operation access for each authority level to enhance operation safety

Operation Log

- Operation log for different user accounts to trace/analyze possible causes of malfunctions
- Provides comprehensive information for managers to analyze the operating habits of different users and improve efficiency

Time	Date	User	Level	Screen Description	Action	Address	Pre Value	Change
13:02:08	09/29/2020		0	Screen_Maintained_0	Set Val	$0.0	0	1
13:02:20	09/29/2020		0	Screen_Maintained_0	Login	$10.0		11
13:02:20	09/29/2020	11	1	Screen_Maintained_0	Set Val	$10.0	0	1
13:02:23	09/29/2020	11	1	Screen_Numeric Entry	Set Val	$100	0	99
13:02:28	09/29/2020	11	1	Screen_Maintained_0	Set Val	$10.0	1	0
13:02:31	09/29/2020	11	1	Screen_Maintained_0	Set Val	$10.0	0	1
13:02:34	09/29/2020	11	1	Screen_Numeric Entry	Set Val	$100	99	88
13:02:37	09/29/2020	11	1	Screen_Maintained_0	Set Val	$0.0	0	1
13:03:04	09/29/2020	11	1	Screen_Numeric Entry	Set Val	$100	88	55
13:03:09	09/29/2020	11	1	Screen_Numeric Entry	Set Val	$100	55	33
13:03:10	09/29/2020	11	1	Screen_Maintained_0	Set Val	$10.0	1	0
13:03:12	09/29/2020	11	1	Screen_Maintained_0	Set Val	$10.0	0	1
13:03:16	09/29/2020	11	1	Screen_Numeric Entry	Set Val	$100	33	123

Cloud Integration

M Type W Type H Type I Type E Type D Type

Only With Ethemet

FTP Server

- Built-in FTP server to update recipes or PDF files, and backup historical data, operation log and alarms



VNC Server

- Built-in VNC server allows remote monitoring and operating of the DOP-100 Series via VNC Client APP (Windows, iOS, Android)
- Lock function: block remote operation during on-site operation to avoid unsynchronized commands. VNC server allows remote monitoring but not remote operation when the lock function is on



Web Monitoring

- Allows direct monitoring of register data via web page, and requires no additional software installation



Hardware Specifications

Advanced HMI

Model		Advanced Narrow Frame Type		
		DOP-103WQ	DOP-107WV	DOP-110WS
LCD Module	Display	4.3" TFT LCD	7" TFT LCD	10.1" TFT LCD
	Color	65,536		
	Resolution (Pixels)	480 x 272	800 x 480	1024 x 600
	Back Light	LED Back Light		
	Back Light Brightness (cd/m^2)	400	450	450
	Back Light Life (Hour) *1	10,000	20,000	30,000
	Display Area	95.04 x 53.856 mm	154.08 x 85.92 mm	225.52 x 128.10 mm
MCU		ARM Cortex-A8 (800MHz)		
Flash ROM (Bytes)		256 MB		
RAM (Bytes)		512 MB		
Touch Panel		Four-wire resistor, over 10,000,000 pressing times		
Buzzer		Multi-Tone Frequency (2K ~ 4K Hz) / 80dB		
Ethernet Interface		1 Port *2, 10/100 Mbps auto-sensing		
USB		1 USB Slave Ver 2.0 / 1 USB Host Ver 2.0		
SD		N/A		SD x 1
Serial COM Port	COM1	RS-232 (supports hardware flow control) / RS-485 *2	RS-232 (supports hardware flow control)	
	COM2	RS-422 / RS-485 *2	RS-232 (supports hardware flow control) / RS-485 *2	
	COM3	N/A	RS-422 / RS-485 *2	
RTC		Built-in		
Cooling		Natural air circulation		
Certification		CE / UL		
Waterproof		IP65 / NEMA4 / UL Type 4X (indoor use only)		
Operation Voltage *3		DC +24V (-15% ~ 15%) *2		
Voltage Endurance		A599V for 1 minute (between charging DC24 terminal and FG terminals)		
Power Consumption *5		Max. 5.8 W *3	Max. 8.4 W *3	Max. 11 W *3
Backup Battery		3V lithium battery CR2032 × 1		
Backup Battery Life		Depends on the temperature used and the conditions of usage, usually about 3 years or more at 25° C		
Operating Temperature		0°C ~ 50°C		
Storage Temperature		-20 °C ~ 60 °C		
Ambient Humidity		10% ~ 90% RH (0 ~ 40° C), 10% ~ 55% RH (41 ~ 50° C), Pollution Degree 2		
Vibration		IEC 61131-2 compliant 5Hz ~ 8.3Hz = Continuous: 3.5mm, 8.3Hz ~ 150Hz = Continuous: 1.0g		
Shock		IEC 60068-2-27 compliant 15g peak for 11ms duration, X, Y, Z, directions for 6 times		
Dimensions (W) x (H) x (D) mm		137 x 103 x 37.1	196 x 136 x 39	270 x 180.9 x 47.75
Mounting dimension (W) x (H) mm		118.8 x 92.8	186.8 x 126.8	255 x 170.5
Weight		280 g	560g	1,100g

1) The half-life of a backlight is defined as the original luminance being reduced by 50% when the maximum driving current is supplied to an HMI.
2) Built-in power isolation
3) An isolated power supply is recommended.
4) Some models are in the process of application for UL and KCC certification. For more information, please consult our distributors.
5) The value of the power consumption indicates the electrical power consumed by the HMI with no peripheral devices connected.
6) The content of this catalogue may be revised without prior notice. Please consult our distributors or download the most updated version at http://www.deltaww.com

Advanced HMI

Model		Advanced Narrow Frame Type		Advanced Multimedia Type	
		DOP-112WX	DOP-115WX	DOP-112MX	DOP-115MX
LCD Module	Display	12" TFT LCD	15" TFT LCD	12" TFT LCD	15" TFT LCD
	Color	24bit			
	Resolution (Pixels)	1024 x 768			
	Back Light	LED Back Light			
	Back Light Brightness (cd/m^2)	500	450	500	450
	Back Light Life (Hour) *1	50,000			
	Display Area	245.76 x 184.32 mm	304.1 x 228.1 mm	245.76 x 184.32 mm	304.1 x 228.1 mm
MCU		Dual Core 1GHz			
Flash ROM (Bytes)		8GB			
RAM (Bytes)		DDR3 1000MHz 1GB			
Touch Panel		Four-wire resistor, over 10,000,000 pressing times			
Buzzer		Multi-Tone Frequency (2K ~ 4K Hz) / 85dB			
Ethernet Interface		2 Port, 100M bps x 2			
USB		1 Mini USB Slave Ver 2.0 / 1 USB Host Ver 2.0			
SD		SD x 1			
Serial COM Port	COM1	RS-232 (supporting flow control) / RS485 *2			
	COM2	RS-422 / RS485 *2			
	COM3	RS-232 (supporting flow control) / RS-485 *2			
	COM4	RS-422 / RS485			
RTC		Built-in			
Cooling		Natural air circulation			
Certification		CE / UL			
Waterproof		IP65 / NEMA4 / UL Type 4X (indoor use only)			
Operation Voltage *3		DC +24V (-15% ~ 15%) *2			
Voltage Endurance		A599V for 1 minute (between charging DC24 terminal and FG terminals)			
Power Consumption *5		Max. 16.08W	Max. 21.12W	Max. 16.08W	Max. 21.12W
Backup Battery		3V lithium battery CR2032 × 1			
Backup Battery Life		Depends on the temperature used and the conditions of usage, usually about 3 years or more at 25° C			
Operation Temperature		0°C ~ 50°C			
Storage Temperature		-20°C ~ 60°C			
Ambient Humidity		10% ~ 90% RH (0 ~ 40° C), 10% ~ 55% RH (41 ~ 50° C), Pollution Degree 2			
Viberation		IEC 61131-2 compliant 5Hz ~ 8.3Hz = Continuous: 3.5mm, 8.3Hz ~ 150Hz = Continuous: 1.0g			
Shock		IEC 60068-2-27 compliant 15g peak for 11ms duration, X, Y, Z, directions for 6 times			
Dimensions (W) x (H) x (D) mm		317.4 x 246.4 x 52.7	387.7 x 295.7 x 63.5	317.4 x 246.4 x 52.7	387.7 x 295.7 x 63.5
Mounting dimension (W) x (H) mm		302.7 x 228.7	372.4 x 283.7	302.7 x 228.7	372.4 x 283.7
Weight		2110g	3200g	2110g	3200g

1) The half-life of a backlight is defined as the original luminance being reduced by 50% when the maximum driving current is supplied to an HMI.
4) Built-in power isolation
5) An isolated power supply is recommended.
4) Some models are in the process of application for UL and KCC certification. For more information, please consult our distributors.
7) The value of the power consumption indicates the electrical power consumed by the HMI with no peripheral devices connected.
8) The content of this catalogue may be revised without prior notice. Please consult our distributors or download the most updated version at http://www.deltaww.com

Hardware Specifications

Standard HMI

Model		Standard General Type			
		DOP-105CQ	DOP-107CV	DOP-110CS	DOP-110CG
LCD Module	Display	5.6" TFT LCD	7" TFT LCD	10" TFT LCD	10.4" TFT LCD
	Color	65,536			
	Resolution (Pixels)	320 x 234	800 x 480	1024 x 600	800 x 600
	Back Light	LED Back Light			
	Back Light Brightness (cd/m^2)	200	400	300	300
	Back Light Life (Hour) *1	20000			
	Display Area	113.28 x 84.70 mm	154.08 X 85.92 mm	226 X 128.7 mm	211.2 x 158.4 mm
MCU		ARM Cortex-A8 (800MHz)			
Flash ROM (Bytes)		256 Mbytes			
RAM (Bytes)		256 Mbytes			
Touch Panel		Four-wire resistor, over > 10,000,000 pressing times			Four-wire resistor, over > 1,000,000 pressing times
Audio Output	Buzzer	Multi-Tone Frequency (2K ~ 4K Hz) / 80dB			
	AUX	N/A			
USB		1 USB Slave Ver 2.0 / 1 USB Host Ver 2.0			
SD		N/A			
Serial COM Port	COM1	RS-232 (supports hardware flow control)*2			
	COM2	RS-232 (supports hardware flow control) / RS-485 *2			
	COM3	RS-422 / RS-485*2			
RTC		Built-in			
Cooling		Nature air circulation			
Certification		CE / UL (please equip shielding cables and linefilters with capacity of 300ohm/100MHz)			
Waterproof		IP65 / NEMA4 / UL Type 4X (indoor use only)			
Operation Voltage *3		DC +24V (-15% ~ +15%)(please equip isolated-type power supplies) Supplied by Class 2 or SELV circuit (isolated from MAINS by double insulation)			
Voltage Endurance		A500V for 1 minute (between charging DC24 terminal and FG terminals)			
Power Consumption *5		Max. 6.86 W *3	Max. 8.5 W *3	Max. 10.4 W *3	Max. 8W*3
Backup Battery		3V lithium battery CR2032 × 1			
Backup Battery Life		Depends on the temperature used and the conditions of usage, usually about 3 years or more at 25° C			
Operation Temperature		0°C ~ 50°C			
Storage Temperature		-20 °C ~ 60 °C			
Ambient Humidity		10% ~ 90% RH (0 ~ 40° C), 10% ~ 55% RH (41 ~ 50° C), Pollution Degree 2			
Vibration		IEC 61131-2 compliant 5Hz ~ 8.3Hz = Continuous: 3.5mm, 8.3Hz ~ 150Hz = Continuous: 1.0g			
Shock		IEC 60068-2-27 compliant 15g peak for 11ms duration, X, Y, Z, directions for 6 times			
Dimensions (W) x (H) x (D) mm		184 x 144 x 50	215 x 161 x 61.2	272 x 200 x 61	229 x 224 x 46.8
Mounting dimension (W) x (H) mm		172.4 x 132.4	196.9 x 142.9	261.3 x 189.3	285.2 x 210.2
Weight		670 g	970 g	1330g	1735 g

1) The half-life of a backlight is defined as the original luminance being reduced by 50% when the maximum driving current is supplied to an HMI.6
2) Built-in power isolation
3) An isolated power supply is recommended.
4) Some models are in the process of application for UL and KCC certification. For more information, please consult our distributors.
5) The value of the power consumption indicates the electrical power consumed by the HMI with no peripheral devices connected.
6) The content of this catalogue may be revised without prior notice. Please consult our distributors or download the most updated version at http://www.deltaww.com

Standard HMI

Model		Standard Ethernet Type (2 COM)	
		DOP-107EG	DOP-107EV
LCD Module	Display	7" TFT LCD	7" TFT LCD
	Color	65,536	
	Resolution (Pixels)	800 x 600	800 x 480
	Back Light	LED Back Light	
	Back Light Brightness (cd/m^2)	450	400
	Back Light Life (Hour) *1	20000	20000
	Display Area	141 X 105.75 mm	154.08 X 85.92 mm
MCU		ARM Cortex-A8 (800MHz)	
Flash ROM (Bytes)		256 Mbytes	
RAM (Bytes)		256 Mbytes	
Touch Panel		Four-wire resistor, over > 10,000,000 pressing times	
Audio Output	Buzzer	Multi-Tone Frequency (2K ~ 4K Hz) / 80dB	
	AUX	Stereo output	N/A
Ethernet Interface		1 Port *2, 10/100 Mbps auto-sensing	
USB		1 USB Slave Ver 2.0; 1 USB Host Ver 2.0	
SD		SD x 1	N/A
Serial COM Port	COM1	RS-232 (supports hardware flow control)*2	
	COM2	RS-232 (supports hardware flow control) / RS-485 *2	
	COM3	RS-422 / RS-485*2	
RTC		Built-in	
Cooling		Natural air circulation	
Certification		CE / UL (please equip Shielding cables and linefilters with capacity of 300ohm/100MHz)	
Waterproof		IP65 / NEMA4 / UL Type 4X (indoor use only)	
Operation Voltage *3		DC +24V (-15% ~ +15%)(please equip isolated-type power supplies) Supplied by Class 2 or SELV circuit (isolated from MAINS by double insulation)	
Voltage Endurance		A500V for 1 minute (between charging DC24 terminal and FG terminals)	
Power Consumption *5		Max. 8.4 W *3	Max. 8.76 W *3
Backup Battery		3V lithium battery CR2032 × 1	
Backup Battery Life		Depends on the temperature used and the conditions of usage, usually about 3 years or more at 25° C	
Operating Temperature		0°C ~ 50°C	
Storage Temperature		-20 °C ~ 60 °C	
Ambient Humidity		10% ~ 90% RH (0 ~ 40° C), 10% ~ 55% RH (41 ~ 50° C), Pollution Degree 2	
Vibration		IEC 61131-2 compliant 5Hz ~ 8.3Hz = Continuous: 3.5mm, 8.3Hz ~ 150Hz = Continuous: 1.0g	
Shock		IEC 60068-2-27 compliant 15g peak for 11ms duration, X, Y, Z, directions for 6 times	
Dimensions (W) x (H) x (D) mm		184 x 144 x 51.5	215 x 161 x 61.2
Mounting dimension (W) x (H) mm		172.4 x 132.4	196.9 x 142.9
Weight		800 g	970g

1) The half-life of a backlight is defined as the original luminance being reduced by 50% when the maximum driving current is supplied to an HMI.
2) Built-in power isolation
3) An isolated power supply is recommended.
4) Some models are in the process of application for UL and KCC certification. For more information, please consult our distributors.
5) The value of the power consumption indicates the electrical power consumed by the HMI with no peripheral devices connected.
6) The content of this catalogue may be revised without prior notice. Please consult our distributors or download the most updated version at http://www.deltaww.com

Hardware Specifications

Standard HMI

Model		Standard Ethernet Type (3 COM)			
		DOP-107IV	DOP-108IG	DOP-110IS	DOP-110IG
LCD Module	Display	7" TFT LCD	8" TFT LCD	10.1" TFT LCD	10.4" TFT LCD
	Color	65,536			
	Resolution (Pixels)	800 x 480	800 x 600	1024 x 600	800 x 600
	Back Light	LED Back Light			
	Back Light Brightness (cd/m^2)	400	250	300	300
	Back Light Life (Hour) *1	20000			
	Display Area	152.4 x 91.44 mm	162 x 121.5 mm	226 x 128.7 mm	211.2 x 158.4 mm
MCU		ARM Cortex-A8 (800MHz)			
Flash ROM (Bytes)		256 Mbytes			
RAM (Bytes)		256 Mbytes			
Touch Panel		Four-wire resistor, over > 10,000,000 pressing times			
Audio Output	Buzzer	Multi-Tone Frequency (2K ~ 4K Hz) / 80dB			
	AUX	N/A	Stereo output		
Ethernet Interface		1 Port*2, 10/100 Mbps auto-sensing			
USB		1 USB Slave Ver 2.0 / 1 USB Host Ver 2.0			
SD		SD x 1			
Serial COM Port	COM1	RS-232 (supports hardware flow control)*2			
	COM2	RS-232 (supports hardware flow control) / RS-485 *2			
	COM3	RS-232 (supports hardware flow control) / RS-422 / RS-485*2			
RTC		Built-in			
Cooling		Nature air circulation			
Certification		CE / UL (please equip shielding cables and linefilters with capacity of 300ohm/100MHz)			
Waterproof		IP65 / NEMA4 / UL Type 4X (indoor use only)			
Operation Voltage *3		DC +24V (-15% ~ +15%)(please equip isolated-type power supplies) Supplied by Class 2 or SELV circuit (isolated from MAINS by double insulation)			
Voltage Endurance		A500V for 1 minute (between charging DC24 terminal and FG terminals)			
Power Consumption *5		Max. 12W *3	Max. 9.88W *3	Max. 9.6W *3	Max. 9.6W*3
Backup Battery		3V lithium battery CR2032 × 1			
Backup Battery Life		Depends on the temperature used and the conditions of usage, usually about 3 years or more at 25° C			
Operation Temperature		0°C ~ 50°C			
Storage Temperature		-20°C ~ 60°C			
Ambient Humidity		10% ~ 90% RH (0 ~ 40° C), 10% ~ 55% RH (41 ~ 50° C), Pollution Degree 2			
Vibration		IEC 61131-2 compliant 5Hz ~ 8.3Hz = Continuous: 3.5mm, 8.3Hz ~ 150Hz = Continuous: 1.0g			
Shock		IEC 60068-2-27 compliant 15g peak for 11ms duration, X, Y, Z, directions for 6 times			
Dimensions (W) x (H) x (D) mm		215 x 161 x 61.2	227.1 x 174.1 x 61	272.6 x 200.6 x 54	299 x 224 x 46.8
Mounting dimension (W) x (H) mm		196.9 x 142.9	219.4 x 166.5	261.3 x 189.3	285.2 x 210.2
Weight		970g	1226g	1130g	1600g

1) The half-life of a backlight is defined as the original luminance being reduced by 50% when the maximum driving current is supplied to an HMI.6
2) Built-in power isolation
3) An isolated power supply is recommended.
4) Some models are in the process of application for UL and KCC certification. For more information, please consult our distributors.
5) The value of the power consumption indicates the electrical power consumed by the HMI with no peripheral devices connected.
6) The content of this catalogue may be revised without prior notice. Please consult our distributors or download the most updated version at http://www.deltaww.com

Basic HMI

Model		Basic Type		Basic Ethernet Type
		DOP-103BQ	DOP-107BV	DOP-107DV
LCD Module	Display	4.3" TFT LCD	7" TFT LCD	7" TFT LCD
	Color	65,536		
	Resolution (Pixels)	480 x 272	800 x 480	800 x 400
	Back Light	LED Back Light		
	Back Light Brightness (cd/m^2)	400		
	Back Light Life (Hour) *1	20000		
	Display Area	95.04 x 53.856 mm	154.08 x 85.92 mm	154.08 x 85.92 mm
MCU		ARM Cortex-A8 (800MHz)		
Flash ROM (Bytes)		256 Mbytes		
RAM (Bytes)		256 Mbytes		
Touch Panel		Four-wire resistor, over > 10,000,000 pressing times		
Audio Output	Buzzer	Multi-Tone Frequency (2K ~ 4K Hz) / 80dB		
	AUX	N/A		
Ethernet Interface		N/A	N/A	1 Port, 10/100 Mbps auto-sensing*2
USB		1 USB Slave Ver 2.0 / 1 USB Host Ver 2.0		
SD		N/A		
Serial COM Port	COM1	RS-232/RS-485 (supports hardware flow control)*2		
	COM2	RS-422 / RS-485*2		
	COM3	N/A		
RTC		Built-in		
Cooling		Nature air circulation		
Certification		CE / UL (please equip shielding cables and linefilters with capacity of 300ohm/100MHz)		
Waterproof		IP65 / NEMA4 / UL Type 4X (indoor use only)		
Operation Voltage *3		DC +24V (-15% ~ +15%)(please equip isolated-type power supplies) Supplied by Class 2 or SELV circuit (isolated from MAINS by double insulation)		
Voltage Endurance		A500V for 1 minute (between charging DC24 terminal and FG terminals)		
Power Consumption *5		Max. 5.67W *3	Max. 8.6W *3	Max. 8.8W *3
Backup Battery		3V lithium battery CR2032 × 1		
Backup Battery Life		Depends on the temperature used and the conditions of usage, usually about 3 years or more at 25° C		
Operation Temperature		0°C ~ 50°C		
Storage Temperature		-20°C ~ 60°C		
Ambient Humidity		10% ~ 90% RH (0 ~ 40° C), 10% ~ 55% RH (41 ~ 50° C), Pollution Degree 2		
Vibration		IEC 61131-2 compliant 5Hz ~ 8.3Hz = Continuous: 3.5mm, 8.3Hz ~ 150Hz = Continuous: 1.0g		
Shock		IEC 60068-2-27 compliant 15g peak for 11ms duration, X, Y, Z, directions for 6 times		
Dimensions (W) x (H) x (D) mm		137 x 103 x 37.1	215 x 161 x 35.5	215 x 161 x 35.5
Mounting dimension (W) x (H) mm		118.8 x 92.8	196 x 142.9	196 x 142.9
Weight		280g	700g	700g

1) The half-life of a backlight is defined as the original luminance being reduced by 50% when the maximum driving current is supplied to an HMI.6
2) Built-in power isolation
3) An isolated power supply is recommended.
4) Some models are in the process of application for UL and KCC certification. For more information, please consult our distributors.
5) The value of the power consumption indicates the electrical power consumed by the HMI with no peripheral devices connected.
6) The content of this catalogue may be revised without prior notice. Please consult our distributors or download the most updated version at http://www.deltaww.com

Hardware Specifications

Handheld HMI

Model		Handheld HMI			
		DOP-107HS4xx	DOP-107HE4xx	DOP-107HE4xxZM	DOP-107HE47xZD
LCD Module	Display	7" TFT LCD			
	Color	65536			
	Resolution (Pixels)	800 x 480			
	Back Light	LED Back Light			
	Back Light Brightness (cd/m^2)	400	450	450	
	Back Light Life (Hour) *1	10,000	20,000	30,000	
	Display Area	154.08 x 85.92 mm			
MCU		ARM Cortex-A8 (800MHz)			
Flash ROM (Bytes)		256 MB			
RAM (Bytes)		512 MB			
Touch Panel		Four-wire resistor, over > 10,000,000 pressing times			
Buzzer		Multi-Tone Frequency (2K ~ 4K Hz) / 80dB			
Ethernet Interface		N/A	1 Port *2, 10/100 Mbps auto-sensing		1 Port *2, 10/100 Mbps auto-sensing
USB		1 USB Slave Ver 2.0			
SD		SD/SDHC			
Serial COM Port/Communication		RS-232/ RS-485	N/A		N/A
Emergency stopswitch		B contact x 2		A contact x 1/B contact x 1	
		Rated voltage: < DC 30V Maximum rated current: 1AMinimum allowable load: DC 5V / 1 mAComplies with IEC60947-5-1, EN60947-5-1, IEC60947-5-5, EN60947-5-5, UL 508, CSA C22.2 No.14, GB 14085.5			
3-position operation switch		A contact x 1			
		Rated voltage: < DC 30VMaximum rated current: 700 mAMinimum allowable load: DC 3V / 5 mAComplies with EN/IEC60947-5-8, IEC60947-5-1, EN60947-5-1, JIS C8201-5-1, UL508, CSA C22.2 NO. 14Applicable standards for use with ISO12100-1,-2/EN12100-1,-2, IEC60204-1/EN60204-1, ISO11161/prEN11161, ISO10218/EN775, ANSI/RIA R15.06, ANSI B11.19			
MPG		Rated voltage: < DC 24V Resolution: 50(P/R) Output waveform: square waveOutput phase: A, B Phase difference between A and B: 90° ± 45° Maximum frequency response: 200 Hz			
Auxiliary keyboard		15 Function Keys			21 Function Keys
Cable length		5 m (when end of model name = 5) 10 m (when end of model name = A)			
Calendar		Built-in			
Cooling method		Natural cooling			
Certification		CE			
Protection rating		IP54			
Operating voltage *3		DC +24V (-15% ~ +15%)*2 (supplied by SELV circuits (isolated from MAINS by double insulation))			
Leakage current		AC500V for one minute (between DC24 and FG terminals)			
Power consumption*5		4.896W			
Backup battery		3V lithium battery CR2450 × 1			
Backup battery life		About 5 years or more at 25°C (77°F)(subject to operation temperature and condition)			
Operation temperature		0°C ~ 40°C			
Storage temperature		-20 °C ~ 60 °C			
Operating environment		10% ~ 90% RH (0 ~ 40° C), 10% ~ 55% RH (41 ~ 50° C), Pollution Degree 2			
Vibration resistance		IEC 61131-2 compliant 5Hz ~ 8.3Hz = Continuous: 3.5mm, 8.3Hz ~ 150Hz = Continuous: 1.0g			
Shock resistance		IEC 60068-2-27 compliant 15g peak for 11ms duration, X, Y, Z, directions for 6 times			
Dimensions (W) x (H) x (D) mm		257.4 x 170.3 x 71.8 (emergency stop switch and hook included)			
Weight		750 g (cable excluded)			

1) The half-life of a backlight is defined as the original luminance being reduced by 50% when the maximum driving current is supplied to an HMI.6
2) Built-in power isolation
3) An isolated power supply is recommended.
4) Some models are in the process of application for UL and KCC certification. For more information, please consult our distributors.
5) The value of the power consumption indicates the electrical power consumed by the HMI with no peripheral devices connected.
6) The content of this catalogue may be revised without prior notice. Please consult our distributors or download the most updated version at http://www.deltaww.com

Model Description

DOP - 1 07 W V

Product Name
DOP : Delta Operation Panel

Series
1 : 100 Series HMI

Resolution	
G: SVGA TFT (800x)	Q: WQVGA TFT (480x)
S: WSVGA TFT (1024x)	V: WVGA TFT (800x)
X: XGA TFT (1024x)	Z: No Display (Zero)

Type
B: Basic Type
D: Basic Ethernet Type
C: Standard General Type
E: Standard Ethernet Type (2 COM)
I: Standard Ethernet Type (3 COM)
W: Advanced Narrow Frame Type
M: Advanced Multimedia Type

Display Sizes				
00: Zero	03: 4.3"	05: 5.6"	7: 7"	8: 8"
10: 10.1"/10.4"	12: 12"	15: 15"		

DOP - 1 07 HS 4 6 5 ZM

Product Name
DOP : Delta Operation Panel

Series
1 : 100 Series HMI

Wire
ZM / ZD: D-Sub 25 pin Connector

Outgoing wire length
5: 5 meter
A: 10 meter

External device
2 : Without hand wheel, SD card + 15 Keys
6: With hand wheel, SD card + 15 keys
7: With hand wheel, SD card + 21 keys

Resolution
4: WVGA

Type
HS: Standard type
HE: Ethernet type

Display Size				
00: Zero	03: 4.3"	05: 5.6"	7: 7"	8: 8"
10: 10.1"/10.4"	12: 12"	15: 15"		

Dimensions Unit: mm (inches)

• DOP-103WQ



Note :
T=1.6mm~3mm(0.063"~0.12")

• DOP-107WV



Note :
T=1.6mm~6mm(0.063"~0.24")

• DOP-110WS



Note :
T=1.6mm~6mm(0.063"~0.24")

• DOP-107HS4 / DOP-107HE4



Dimensions Unit: mm (inches)

• DOP-112MX / DOP-112WX



Note:
T=1.6 mm ~ 6 mm(0.063" ~ 0.24")

• DOP-115MX / DOP-115WX



Note:
T=1.6 mm ~ 6 mm(0.063" ~ 0.24")

• DOP-107IV



Note:
T=1.6 mm ~ 6 mm(0.063" ~ 0.24")

Dimensions Unit: mm (inches)

• DOP-108IG



• DOP-110IS



• DOP-110IG



• DOP-107EV



Note:
T=1.6 mm ~ 6 mm(0.063" ~ 0.24")

• DOP-107EG



Note:
T=1.6 mm ~ 6 mm(0.063" ~ 0.24")

• DOP-105CQ



Dimensions Unit: mm (inches)

• DOP-107CV



Note:
T=1.6 mm ~ 6 mm(0.063" ~ 0.24")

• DOP-110CS



Note:
T=1.6 mm ~ 6 mm(0.063" ~ 0.24")

• DOP-110CG



• DOP-107DV



Note:
T=1.6 mm~6 mm(0.06"~0.24")

• DOP-103BQ



Note :
T=1.6mm~3mm(0.063"~0.12")

• DOP-107BV



Note:
T=1.6 mm~6 mm(0.06"~0.24")

Polígono Industrial A Reigosa Parcela B-33

36828 Ponte Caldelas

Pontevedra - España

Telf. (+34) 986 872 010

E-mail: egasen@egasen.com

Web: www.egasen.com